

**SWIFT®****Intelligent Wireless Detectors**

**NOTIFIER®**  
by Honeywell
**Intelligent Detectors****General**

SWIFT® wireless detectors are intelligent (addressable) detectors which provide secure, reliable communication to the Fire Alarm Control Panel (FACP) across a Class A mesh network. Wireless detectors create an opportunity for applications where it is costly (concrete walls/ceilings, buried wires), obtrusive (surface mount conduit), or possibly dangerous (asbestos) to use traditional wired devices. In addition, both wired and wireless devices can be present on the same FACP providing an integrated wired-wireless solution for increased installation potential.

The SWIFT detection line includes a photoelectric, Acclimate®, standard fixed heat, and rate-of-rise heat detectors. The photoelectric detectors transmit a digital representation of smoke density through a wireless mesh to a gateway and on to a FACP. The Acclimate detectors combine a photoelectric chamber and a 135°F fixed temperature heat detector. Acclimate can also transmit an alarm signal due to heat per UL 521. The fixed heat detector and rate-of-rise detectors utilize sensors designed for open area protection with 50 foot spacing capability as approved by UL 521.

All sensors offer addressable code wheels and two LEDs. The LEDs are controlled by the panels. Operation modes include red, green, and amber colors with various solid or blink patterns.

The mesh network within the SWIFT system creates a child-parent relationship between the devices so that each device has two parents providing a second path for communications on every device. If one device can no longer operate for any reason, the rest of the devices can still communicate with each other, directly or through one or more intermediate devices.

The SWIFT system also engages frequency hopping to prevent system interference whether intentional or accidental.

**Features**

- Wireless installation
- Class A mesh network
- Addressable code wheels
- Commercial applications
- UL 268 listed
- Frequency hopping
- Bi-directional communications

**Specifications****PHYSICAL / OPERATING SPECIFICATIONS**

**Height:** 2.4 inches (61 mm) installed in B210W base

**Diameter:** 6.0 inches (152mm) installed in B210W base

**Device Weight (includes 4 batteries):** 9.2 oz (261 g) installed in B210W base

**Operating Temperature Range:** Photo: 32°F to 120°F (0°C to 49°C); Acclimate with Heat: 32°F to 100°F (0°C to 38°C)



Swift Detector B201 base.jpg

**Intelligent Wireless Detector with B210W base**

**Air Velocity:** Acclimate with Heat: 0 to 4,000 fpm (0 to 20 m/sec)

**Operating Humidity Range:** 10% to 93% non-condensing

**Thermal Ratings:** Fixed Temperature Set Point: 135°F (57°C); Rate-of-Rise Detection: 15°F/min (8.3°C/min)

**ELECTRICAL SPECIFICATIONS**

**Maximum Operating Voltage:** 3.3 VDC

**Maximum Standby Current:** 210µA @ 3.3 VDC (one communication every 23.9 seconds with LED blink enabled)

**Maximum Alarm Current (LED on):** 5 mA @ 3.3 VDC (LED on)

**Radio Frequency Range:** 902-928 MHz

**BATTERY SPECIFICATIONS**

**Battery Type:** 4 Panasonic CR123A or 4 Duracell DL 123A

**Battery Life:** 2 years

**Battery Replacement:** Upon BATTERY LOW or BAT LOW display and/or during annual maintenance

**Agency Listings and Approvals**

Each device complies with part 15 of the FCC rules meaning operation is subject to two conditions.

1) The device may not cause harmful interference and 2) The device must accept any interference received including interference that may cause undesired operation.

The listings and approvals below apply to the basic intelligent wireless detector. In some cases, certain modules may not be listed by certain approval agencies or listing may be in process. Consult factory for latest listing status.

**UL Listed:** S635

**CSFM:** 7272-0028:0271, 7254-0028:0270

**FM Approved**

**FCC ID:** AUBWFSSD

**IC ID:** 573X-WFSSD

## Standards and Codes

The SWIFT Wireless Intelligent Detectors comply with the following UL Standards and with NFPA 72 Fire Alarm System requirements.

UL 864

UL 268

## Ordering Information

**FWD-200P:** Wireless photoelectric smoke detector for use with the FWSG wireless gateway

**FWD-200ACCLIMATE:** Wireless Acclimate detector for use with the FWSG wireless gateway

**FWH-200FIX135:** Wireless fixed-temperature (135° F) heat detector for use with the FWSG wireless gateway

**FWH-200ROR135:** Wireless rate-of-rise (135° F) heat detector for use with the FWSG wireless gateway

**FWSG:** FlashScan® Wireless Gateway.

**B210W:** 6" wireless mounting base.

**W-USB:** Software interface (via USB port) for computers running the SWIFT Tools programming utility.

---

Acclimate® Plus, FlashScan®, NOTIFIER®, and SWIFT® are registered trademarks of Honeywell International Inc. Microsoft® and Windows® are registered trademarks of Microsoft Corporation.  
©2015 by Honeywell International Inc. All rights reserved. Unauthorized use of this document is strictly prohibited.



This document is not intended to be used for installation purposes.  
We try to keep our product information up-to-date and accurate.  
We cannot cover all specific applications or anticipate all requirements.  
All specifications are subject to change without notice.

For more information, contact Notifier. Phone: (203) 484-7161, FAX: (203) 484-7118.  
[www.notifier.com](http://www.notifier.com)